

Zirconite

STAGE 1 – PRE-GLAZE

PREPARES PAINTWORK FOR STAGE 2 GLAZE.

Paint Rectification & Pre-treatment:

All scratches and holograms should be removed using the Surf-ACE compound system.

Stage 1 Pre-Glaze is used to:

- Remove wax residues and/or underbodyseal overspray.
- Provide correct 'key' to paintwork to accept Stage 2 Glaze sealant polish

Directions:

Apply section by section with soft cotton cloth. Do not wipe dry. Allow to dry out on paint surface.

Typical Specification:

Composition	: Aliphatic hydrocarbon solvent blend.
Appearance	: Clear liquid
Colour	: Water white
S.G.	: 0.77
Odour	: Mild
F.P.	: >40°C
Shelf Life	: Minimum 2 years in unopened containers at ambient temperature.
Packaging	: 125ml & 1L Plastic Containers.

Zirconite Pre-Glaze is a Trade Mark of Concept Chemicals & Coatings Ltd

CODE: 473

CONCEPT CHEMICALS & COATINGS LTD

Felt Court, Windmill Lane Industrial Estate, Denton, Manchester M34 3RB, England.
Tel: +44 (0)161 335 0213 Fax: +44 (0)161 335 0214 email: info@conceptchemicals.com

In accordance with our policy of continuous improvement we reserve the right to amend specification without prior notice

www.conceptchemicals.com